

WSTB-120

Digital SD Cable Receiver

Main Feature

- Fully DVB-C compliant
- Support MPEG-2 MP@HL, H.264
- Conax CAS Embedded
- SCART and RCA Video output
- 2000 channels TV and radio programs
- 7 days electronic program guide (EPG)
- One touch & Schedule Recording Function
- Timeshift
- Support USB 2.0 and OTA software upgrade
- USB 2.0 Interface
- OSD teletext and subtitle function supported
- Multi-Audio supported
- Automatic NIT channel search
- Favorite program setting
- Multi-language OSD supported
- LCN supported



Specification

| | | |
|----------------|-----------------------|------------------------------------|
| Tuner | RF Connector Input | F type |
| | RF Connector Output | IEC type |
| | Frequency Range | 51-860MHz |
| | Input impedance | 75Ω |
| | IF bandwidth | 8 MHz |
| | Demodulation | 16/32/64/128/256QAM |
| | Symbol rate | 1~7Mbps |
| Video Decoding | Transport stream | ISO/IEC 13818-2 |
| | Profile Level | MPEG-2 MP@HL |
| | Aspect Ratio | 4:3, 16:9 |
| | Video Resolution | 720×576 |
| Audio Decoding | Video Sync Scope | 300mVp-p |
| | Standard | ISO/IEC 13818-3 |
| | Audio Decoding | MPEG-1 layer I/II, MPEG-2 layer II |
| | Audio Mode | Single/Dual mono/Stereo |
| | Sample Frequency | 16/22.05/24/32/44.1/48 kHz |
| | Audio Output Level | 0-6 dBu |
| | Volume Level | 32 Levels |
| Rear panel | RF Input Connector | F Port |
| | RCA | CVBS×1,A-L×1,A-R×1 |
| | Scart | CVBS, RGB |
| | S/PDIF | Coaxial Digital Audio Output |
| | USB | USB 2.0 |
| | LAN | RJ-45 |
| Power Supply | Power Supply | DC 5V/2 A |
| | Adaptor Input Voltage | AC 200~240V 50/60Hz |
| | Power consumption | Standby <1W, Working <6W |